



Copper tubular terminal ends- Economy Series- Light duty 2.5 mm² to 1000 mm²

- Material** : Copper tube to BS 1977/ IS 191
Finish : Electro-tinned or uncoated
Features : Available without inspection window upon request
 Available in 45° and 90° barrel orientations
 Available with bell mouth
 RoHS compliant

PC PART NO.	CROSS SECTION MM ²	ØE	A	C	D	F	B	K	H	G	J-LENGTH
PCLV-01	2.5	5.2	2.4	4	9	1	7	3	5	5	20
PCLV-02	4	6.5	3.2	4.8	11	1	7	3	6	6	22
PCLV-03	6	6.5	3.8	5.5	11	1	9	3	6	6	24
PCLV-04	10	6.5	4.4	6.2	11	1.3	9	3	6	6	24
PCLV-05	16	6.5	5.3	7.1	11	1.6	12	4	8	6	30
PCLV-06	25	6.5	7	9	13	2	12	5	12	8	37
PCLV-07	35	6.5	8	10	15	2	12	5	12	8	37
PCLV-08	35	8.2	8	10	15	2	12	5	12	8	37
PCLV-09	50	6.5	9.2	11.2	16	2	16	8	12	9	45
PCLV-10	50	8.2	9.2	11.2	16	2	16	8	12	9	45
PCLV-11	50	10.2	9.2	11.2	16	2	16	8	12	9	45
PCLV-12	70	8.2	11.5	13.8	20	2.3	18	10	15	13	56
PCLV-13	70	10.2	11.5	13.8	20	2.3	18	10	15	13	56
PCLV-14	70	12.7	11.5	13.8	20	2.3	18	10	15	13	56
PCLV-15	95	10.2	12.8	15.6	23	2.8	20	10	15	13	58
PCLV-16	95	12.7	12.8	15.6	23	2.8	20	10	15	13	58
PCLV-17	120	10.2	14.8	17.8	26	3	22	10	16	14	62
PCLV-18	120	12.7	14.8	17.8	26	3	22	10	16	14	62
PCLV-19	120	16.2	14.8	17.8	26	3	22	10	16	14	62
PCLV-20	150	10.2	16	19.6	28	3.6	26	11	18	15	70
PCLV-21	150	12.7	16	19.6	28	3.6	26	11	18	15	70
PCLV-22	150	16.2	16	19.6	28	3.6	26	11	18	15	70
PCLV-23	185	12.7	18	22	32	4	30	11	21	21	83
PCLV-24	185	16.2	18	22	32	4	30	11	21	21	83
PCLV-25	225	16.2	20	24	35	4	32	15	24	24	95
PCLV-26	240	16.2	22	26	38	4	34	15	24	24	97
PCLV-27	240	20.3	22	26	38	4	34	15	24	24	97
PCLV-28	300	16.2	24	28.7	42	4.7	36	16	25	25	103
PCLV-29	300	20.3	24	28.7	42	4.7	36	16	25	25	103
PCLV-30	400	20.3	28	33.2	49	5.2	44	18	27	27	116
PCLV-31	500	20.3	30	36	53	6	48	18	27	27	120
PCLV-32	630	20.3	35	41.5	61	6.5	53	20	33	31	137
PCLV-33	800	---	39	46.3	67	7.3	68	25	38	37	165
PCLV-34	1000	---	43	53.8	76	10.8	90	30	45	45	210