



Copper tubular terminal ends- Standard Series- Bell Mount 10 mm² to 300 mm²

- Material** : E-copper DIN EN 13600
Finish : Electro-tinned or uncoated
Features : Flared cable entry for easy inspection
 Available without inspection window part number starting with 'PCLZ'
 Available in 45° and 90° barrel orientations
 RoHS compliant
- Notes** : ¹ Electro-tinned: ending with 'P', uncoated: ending with 'U'
 - for use with copper fine stranded conductors to DIN VDE 60228 or
 copper cable conductors to DIN VDE 0295
 Wire sizes from 16mm² to 500mm² are UL listed

PART NO	CROSS-SECTION MM ²	ØE	ID	W	B	L	PACKING UNITY PCS/BOX
PCLX-10-5		5.5		12	14	27	100
PCLX-10-6		6.5		12	14	27	100
PCLX-10-8	10	8.5	5.5	16	14	29	100
PCLX-10-10		10.5		16	14	31	100
PCLX-10-12		13		19	14	32	100
PCLX-16-5		5.5		13	15	30	100
PCLX-16-6		6.5		13	15	30	100
PCLX-16-8	16	8.5	6.6	16	15	38	100
PCLX-16-10		10.5		17	15	34	100
PCLX-16-12		13		19	15	35	100
PCLX-25-5		5.5		15	17	32	100
PCLX-25-6		6.5		15	17	32	100
PCLX-25-8	25	8.5	7.9	17	17	34	100
PCLX-25-10		10.5		17	17	37	100
PCLX-25-12		13		19	17	38	100
PCLX-35-6		6.5		17	19	35	100
PCLX-35-8		8.5		18	19	37	100
PCLX-35-10	35	10.5	9.2	18	19	40	100
PCLX-35-12		13		19	19	41	100
PCLX-35-14		15		21	19	43	100
PCLX-50-6		6.5		21	21	41	50
PCLX-50-8		8.5		21	21	41	50
PCLX-50-10		10.5		21	21	43	50
PCLX-50-12	50	13	11	21	21	46	50
PCLX-50-14		15		23	21	48	50
PCLX-50-16		17		28	21	50	50
PCLX-70-8		8.5		25	25	46	50
PCLX-70-10		10.5		25	25	48	50
PCLX-70-12	70	13	13	25	25	50	50
PCLX-70-14		15		25	25	52	50
PCLX-70-16		17		25	25	54	50

PART NO	CROSS-SECTION MM ²	ØE	ID	W	B	L	PACKING UNITY PCS/BOX
PCLX-95-8		8.5		26	28	52	50
PCLX-95-10		10.5		26	28	52	50
PCLX-95-12	9S	13	14.5	26	28	53	50
PCLX-95-14		15		26	28	55	50
PCLX-95-16		17		26	28	56	50
PCLX-120-10		10.5		30	30	57	50
PCLX-120-12		13		30	30	58	50
PCLX-120-14	120	15	16.2	30	30	58	50
PCLX-120-16		17		30	30	59	50
PCLX-120-20		21		36	30	66	50
PCLX-150-10		10.5		34	32	64	10
PCLX-150-12		13	18	34	32	65	10
PCLX-150-14	150	15		34	32	67	10
PCLX-150-16		17		34	32	68	10
PCLX-150-20		21		40	32	70	10
PCLX-185-12		13		39	35	72	10
PCLX-185-14	185	15	20.6	39	35	72	10
PCLX-185-16		17		39	35	72	10
PCLX-185-20		21		39	35	72	10
PCLX-240-10		10.5		4j	44	80	10
PCLX-240-12		13		4l	44	80	10
PCLX-240-14	240	15	23.1	4l	44	83	10
PCLX-240-16		17		q	44	83	10
PCLX-240-20		21		qi	44	85	10
PCLX-300-12		13		47	44	96	5
PCLX-300-14		15	26.1	47	44	96	5
PCLX-300-16	300	17		47	44	96	5
PCLX-300-20		21		47	44	96	5