


# POWERCONNECT COMPONENT

## Aluminum tubular terminals ends - Standard Series- Narrow 2.50 mm<sup>2</sup> to 1000 mm<sup>2</sup>



**Material** : Aluminum IS 6061  
**Finish** : Non Coated  
**Notes** : RoHS compliant

PC PART NO	CROSS SECTION MM <sup>2</sup>	ØE	A	C	D	F	B	K	H	G	J-LENGTH
PCLVA-1	2.5	3.2	2	5.5	6.6	3.5	7	3	4	4	18
PCLVA-2	2.5	3.7	2.6	5.5	7	2.9	7	3	4	4	18
PCLVA-3	4	4.2	2.9	5.5	7.2	2.6	7	3	4	4	18
PCLVA-4	4	5.2	2.9	5.5	12	1.2	7	4	7	6	23
PCLVA-5	6	5.2	3.5	5.5	7.5	2	7	4	7	6	24
PCLVA-6	6	6.5	3.5	5.5	12	1.1	7	4	7	6	24
PCLVA-7	10	4.2	3.8	6.2	8.4	2.4	7	4	9	8	28
PCLVA-8	10	6.4	4.4	7.2	9.7	2.8	9	4	9	8	30
PCLVA-9	10	8.2	4.4	7.2	15	1.8	9	4	9	8	30
PCLVA-10	16	6.4	5.4	8.3	11.4	2.9	13	4	11	9	37
PCLVA-11	16	8.2	5.4	8.3	11.4	2.9	13	4	11	9	37
PCLVA-12	16	10.2	5.4	8.3	18	1.8	13	4	11	9	37
PCLVA-13	25	6.4	7	9.7	13.7	2.7	16	7	11	10	44
PCLVA-14	25	8.2	7	9.7	13.7	2.7	16	7	11	10	44
PCLVA-15	25	10.2	7	9.7	20	1.7	16	7	11	10	44
PCLVA-16	25	12.7	7	9.7	20	1.7	16	7	11	10	44
PCLVA-17	35	6.4	8	10.8	15.4	2.8	18	7	11	11	47
PCLVA-18	35	8.2	8	10.8	15.4	2.8	18	7	11	11	47
PCLVA-19	35	10.2	8	10.8	20	2.1	18	7	11	11	47
PCLVA-20	50	8.2	9.3	13	18.3	3.7	22	8	13	11	54
PCLVA-21	50	10.2	9.3	13	23	2.8	22	8	13	11	54
PCLVA-22	50	12.7	9.3	13	23	2.8	22	8	13	11	54
PCLVA-23	70	8.2	11.4	15.6	22.3	4.4	26	8	13	13	60
PCLVA-24	70	10.2	11.4	15.6	22.3	4.4	26	8	13	13	60
PCLVA-25	70	12.7	11.4	15.6	22.3	4.4	26	8	13	13	60
PCLVA-26	95	10.2	13	17.4	24.6	4.2	28	8	14	14	64
PCLVA-27	95	12.7	13	17.4	24.6	4.2	28	8	14	14	64
PCLVA-28	95	16.2	13	17.4	24.6	4.2	28	8	14	14	64
PCLVA-29	120	10.2	14.7	19.6	28.2	4.6	32	11	15	15	73
PCLVA-30	120	12.7	14.7	19.6	28.2	4.6	32	11	15	15	73
PCLVA-31	120	16.2	14.7	19.6	28.2	4.6	32	11	15	15	73
PCLVA-32	150	10.2	16.5	21.5	30.9	5	34	11	17	17	79
PCLVA-33	150	12.7	16.5	21.5	30.9	5	34	11	17	17	79
PCLVA-34	150	16.2	16.5	21.5	30.9	5	34	11	17	17	79
PCLVA-35	185	10.2	18.5	24	34.6	5.5	36	12	18	18	84
PCLVA-36	185	12.7	18.5	24	34.6	5.5	36	12	18	18	84
PCLVA-37	185	16.2	18.5	24	34.6	5.5	36	12	18	18	84
PCLVA-38	225	12.7	21	27	39	6	40	14	20	20	94
PCLVA-39	240	12.7	21.3	28.2	40.6	6.6	44	14	22	22	102
PCLVA-40	240	16.2	21.3	28.2	40.6	6.6	44	14	22	22	102
PCLVA-41	300	16.2	24.1	31.2	44.2	8.5	47	14	27	27	115
PCLVA-42	300	20.3	24.1	31.2	44.2	7	47	14	27	27	115
PCLVA-43	400	20.3	27.1	35.7	51.5	8.5	56	13	31	30	130
PCLVA-44	500	20.3	30.2	41	58.7	10	60	15	33	32	140
PCLVA-45	625	20.3	35.2	46	66	10	69	16	35	34	154
PCLVA-46	800	---	39	51	73	12	77	25	39	39	180
PCLVA-47	1000	---	43.5	57	81.9	13.5	100	30	45	45	220